

Multipoint M777E/ Multipoint M777P

Centon Generation M777E & M777P multipoint are a multiple hot water outlet heater with a powerful 7.0kW heating elements which gives unlimited capacity hot water supply.

Centon Kenya Limited is the sole importer of Centon Heaters in Kenya and support a three year written warranty of the heating element.

The Generation M777E comes with the following features: Electronic variable temperature control. Earth Leakage Circuit Breaker (ELCB) Anti-leak copper tank

Safety Features

- Flip Start Flow Switch – the electrical supply to the unit will only activate, once the water flows through the system.
- Anti Scalding – with a built in thermal cut out, once the temperature in the system reaches 55°C the power supply is cut off, to the heating element, thereby preventing scalding.
- Anti-Leak Clamp Tank Design – the storage tank in the system has a rubber seal preventing leakage into the system.
- Residual Current Device (RCD) safety – as sensitive as 15 mAmp that would automatically cut off power in the event of current leakage thereby preventing a possible electrocution.
-



No need for expensive mixer tap. Just requires single tap as water temperature can be electronically controlled. No need for pre-heating. It is a true energy saver as it only consumes electricity by heating up water instantly at the time of usage.

The multipoint heater is ideal for supply of hot water to multiple outlets within a home e.g. for the Shower Area and Wash Hand Basin. This is an ideal replacement, for a conventional hot water cylinder, as it gives hot water on demand and also saves on heating costs.

The Multipoint is also available in a Pump model – M777P, which has a built-in booster pump of 120W rating, with a variable speed control, to pressurise the water up to 4 1/2 times.

Technical Specifications

- Heater Electrical Rating – Available in 7.0 kW, 220-240V A.C, 50/60Hz
- Minimum Water Flow Rate – 2 litres/min
- Minimum Water Pressure – 0.14kg f/cm² (2 psi)
- Maximum Water Pressure – 6.0kg f/cm² (85 psi)
- Water Temperature Control – Electronic Control
- Thermal Cut-off – Auto cut-off thermostat : 55°C
- Water Connection – 15mm dia (1/2" BPS)
- Dimensions – 240mm x 360mm x 110mm (H)
- Weight -2.7 Kgs
- Pump electrical rating(motor) -120w,240 A.C,50Hz(for pump models only).



Electronic System



Shower Pump

(PUMP MODELS ONLY)



Flip-Start Switch



Anti-Scalding



Electronic ELCB Safety



Warranty Heating Element



Splash Proof & Anti-Rust



Triple Safety System